

M1440-T200L-0.6



Acousto-Optic Modulator / Frequency Shifter


(PRELIMINARY)

0826

SPECIFICATIONS

Spectral Range:	0.36 > 1.5 μ m
Standard A/R Wavelengths:	0.7-0.9 μ m, 0.6-1.0 μ m *
Optical Power:	10 Watts *
Interaction Medium:	Tellurium Dioxide (TeO ₂)
Acoustic Velocity:	4.2mm/ μ s
Centre Frequency (fc):	200MHz
RF Bandwidth:	>40MHz
Input Impedance:	50 Ω Nominal
VSWR:	<1.5:1 @ fc
Max RF power:	2.0W
Clear Aperture:	3.5mm
Active Aperture:	0.6mmH x 1.5mmW
Static Insertion Loss	< 3%
Reflectivity:	< 1.0% / surface
Laser Polarization:	Any / vertical preferred *
DC Contrast Ratio:	>1000:1 min (>2000:1 typical)

TYPICAL PERFORMANCE *



	633nm	780nm	830nm
Drive Power (theoretical):	0.7 W	1.1 W	1.3W
CW diffraction efficiency, 1.5W max RF:	>85%	>85%	>85%
Bragg Angle:	15.1 mrad	18.6 mrad	19.8 mrad
Separation Angle:	30.1 mrad	37.1 mrad	39.5 mrad

* see foot notes.

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE


ISOMET CORP, 10342 Battleview Parkway, Manassas, VA 20109, USA.

Tel: (703) 321 8301 Fax: (703) 321 8546

E-mail: ISOMET@ISOMET.COM Web Page: WWW.ISOMET.COM

Quality Assured.

In-house: Crystal Growth,
Optical Polishing,
A/R coating, Vacuum Bonding



M1440-T200L-0.6




Acousto-Optic Modulator / Frequency Shifter

(PRELIMINARY)

0826

OUTLINE DRAWING



RF DRIVE ELECTRONICS

Digital modulation: 525F-2

Analog modulation: 532F-2

Dual modulation: 555F-2

* Notes:

- PLEASE SPECIFY OPERATING WAVELENGTH.
- For higher powers please contact Isomet.
- Approximately 5% efficiency difference between v-pol and h-pol for the same RF drive power.
- Estimated efficiency applies to single mode input.

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
 ISOMET CORP, 10342 Battleview Parkway, Manassas, VA 20109, USA.
 Tel: (703) 321 8301 Fax: (703) 321 8546
 E-mail: ISOMET@ISOMET.COM Web Page: WWW.ISOMET.COM

Quality Assured.
 In-house: Crystal Growth,
 Optical Polishing,
 A/R coating, Vacuum Bonding